

Warranty

Commercial Use 2018

Australia's leading Warranties

Major Components	Parts	Commercial Use	
		Parts Warranty	Labour Warranty
Evacuated Tube Solar Collector	Evacuated Tubes	10 Years	1 Year
	Manifold/Heat Exchanger	10 Years	1 Year
	Mounting frame	10 Years	1 Year
Solar Storage Tanks	Vitreous Enamel (SolarArk)	5 years	1 Year
	Stainless Steel	15 Years	1 Year
Components	Solar Controller	1 Year	1 Year
	Sensor Cable	1 Year	1 Year
	Circulating Pump	2 Year	1 Year
	Valves <i>(If supplied by SolarArk)</i>	1 Year	1 Year
	Electric Heating Element	1 Year	1 Year
	Anode	1 Year	1 Year
S20 & S26 Solar Compatible Gas Booster	Gas Heat Exchanger	5 Years	3 Years
	Other components	1 Years	1 Years

Allowable Total Dissolved Solids

Vitreous Enamel Tanks

Stainless Steel Tanks

Solar Collector

Water Quality		Water Quality		Total Dissolved Solids	<600 mg/litre or ppm
Total Dissolved Solids	<600 mg/litre or ppm	Total Dissolved Solids	<600 mg/litre or ppm	Total Hardness	<200 mg/litre or ppm
Total Hardness	<200 mg/litre or ppm	Total Hardness	<200 mg/litre or ppm	Chloride	<250 mg/litre or ppm
Chloride	<300 mg/litre or ppm	Chloride	<250 mg/litre or ppm	Sodium	<150 mg/litre or ppm
Sodium	<150 mg/litre or ppm	Sodium	<150 mg/litre or ppm	Magnesium	<10 mg/litre or ppm
Magnesium	<10 mg/litre or ppm	Magnesium	<10 mg/litre or ppm	PH Levels	7.0 – 8.5
PH Levels	6.5 – 9.5	PH Levels	6.5 – 8.5		
Electrical Conductivity	850 µS/cm	Electrical Conductivity	850 µS/cm		
Dissolved CO ₂	Gas18mg/litre or ppm	Dissolved CO ₂	Gas18mg/litre or ppm		
Saturation Index	+0.4 to 1.0 @ 65°	Saturation Index	+0.4 to 1.0 @ 65°		



www.solarark.com.au
1300670966
info@solarark.com.au

